

Checklist Push Button PK



Please fill out the checklist as completely as possible and send the PDF document to: info@tsl-escha.com

After checking the conformity of the checklist, you will receive a final article drawing in which the product is clearly described. In addition, you will receive an attractive offer according to your specifications.

We would also be happy to complete the checklist together with you. Call us at +49 (0)2353-66796-0

When selecting colors and pictograms according to EN 14752 and EN 16584-1, the backgrounds must be taken into account. Furthermore, for compliance with EN 14752 and TSI-LOC & PAS, appropriate light and sound signals must be taken into account. If you have any questions about this, please do not hesitate to contact us.

CUSTOMER INFORMATION

Company:

Name:

Address:

Phone:

E-Mail:

Date:

Project:

Quantity:

Quantity 1. year:

Quantity 2. year:

Quantity 3. year:

Notes:

1 APPLICATION AREA

Side entry systems for railway vehicles

Pushbutton for help call device and sanitary cells


Buses

Other Applications

2 CONSTRUCTION TYPES


Construction Type 1

Optional mounting screws:
3x DIN 7984 - M4x20 A2




Construction Type 2

Optional mounting screws:
3x DIN 7984 - M4x20 A2




Construction Type 3

Optional mounting screws:
3x similar DIN 7991 - M4x20 A2




Construction Type 4

Optional mounting screws:
3x DIN 7984 - M4x20 A2




Construction Type 5

Without mounting screws:



Construction Type 6


Without mounting screws:



2 CONSTRUCTION TYPES


Construction Type 7

Including mounting material




Construction Type 8

Including mounting material



Construction Type 9

Including mounting material




3 MOUNTING SCREWS (When selecting the Construction Type 1 to 4)

With

Without

4 SCREW ALIGNMENT (When selecting the Construction Type 1 to 6)

Alignment „A“



Alignment „V“



5 CABLE OUTLET

Bottom

Left

Right

6 VARIABLE ADAPTATION TO THE DOOR PROFILE (When selecting the Construction Type 7 and 8)


Angle 0 °

Angle 6 °

Angle 10 °

Angle 15 °

Angle 25 °



7 GLASS THICKNESS (Construction Type 7 and 8)

Construction Type 7: Glass thickness 4-7 mm

Construction Type 8: Glass thickness 4-6 mm

Construction Type 7:

Glass thickness 8-13 mm

Glass thickness

mm

8 MOUNTING RING

The mounting ring is made of plastic.

						
RAL 1023	RAL 2000	RAL 2003	RAL 2004	RAL 3020	RAL 5017	RAL 6024
						
RAL 7035	RAL 7042	RAL 7043	RAL 9004	RAL 9017	RAL 9016	

RAL-Ton oder Farbtan auf Anfrage

9 TOUCH SURFACE COATING TO PROTECT AGAINST GRAFFITI REMOVER

Without

With

Note: The graffiti remover protection offers increased protection of the touch surface against our tested graffiti cleaning chemicals. Please follow the cleaning instructions in the PK52 instructions for use and installation. A list of tested cleaning chemicals can be found on our Website www.tsl-escha.com


10 INSERT RING

When selecting the Construction Type 2, 7 or 8

						
RAL 1023	RAL 2000	RAL 2004	RAL 3003	RAL 3020	RAL 5017	RAL 6024
						
RAL 7035	RAL 7042	RAL 7043	RAL 9004 RAL 9017	RAL 9016		

RAL-Ton oder Farbtan auf Anfrage

11 BRAILLE-LABELING/PRINTING



without Braille

Braille open

Braille stop

Braille on request

without printing

Printing open

Printing stop

Printing on request

color printing

white

black

12 TOUCH SURFACE



flat

raised



tactile arrows open




tactile arrows close

13 PICTOGRAPHS¹⁾

						
B08 RAL 6024/RAL 9006	B09 RAL 5017/RAL 9006	B10 RAL 1023/RAL 9017	B17 RAL 9006/RAL 5017	B20 RAL 7042/RAL 9017	B22 RAL 3020/RAL 9016	B38 RAL 6024/RAL 9016
						
B45 RAL 6024/RAL 9016	B41 RAL 1023/RAL 9017	B25 RAL 9006/RAL 9004	B42 RAL 6024/RAL 9004	B56 RAL 9004/RAL 9016	B66 RAL 1023/RAL 9004	B70 RAL 3020/RAL 9004
						
B71 RAL 5017/RAL 7042	B73 RAL 6024/RAL 9016	B82 RAL 5017/RAL 9004	B116 RAL 3020/RAL 9016	B117 RAL 5017/RAL 9016	B05 RAL 5017/RAL 9006	B07 RAL 3020/RAL 9006
						
B15 RAL 3003/RAL 9006	B24 RAL 6024/RAL 9016	B31 RAL 6024/RAL 9016	B49 RAL 7042/RAL 9016	B54 RAL 3020/RAL 9006	B67 RAL 1023/RAL 9017	B110 RAL 5017/RAL 9016
						
B32 RAL 3020/RAL 9016	B39 RAL 3020/RAL 9016	B46 RAL 3020/RAL 9016	B55 RAL 6024/RAL 9006	B57 RAL 5017/RAL 9006	B114 RAL 6024/RAL 9016	B29 RAL 9006/RAL 9004
						
B43 RAL 3020/RAL 9004	B13 RAL 1023/RAL 9017	B16 RAL 3020/RAL 9006	B40 RAL 6024/RAL 9006	B51 RAL 5017/RAL 9006	B78 RAL 3020/RAL 9016	B81 RAL 6024/RAL 9017

13 PICTOGRAPHS¹⁾

						
B103 RAL 9016/RAL 9017	B109 RAL 9016/RAL 5017	B14 RAL 1023/9017	B21 RAL 1023/9017	B52 RAL 5017/9016	B89 RAL 9006//9004	B75 RAL 5017/9016
						
B100 RAL 5022/RAL 9003	B02 RAL 5017/RAL 9016	B04 RAL 9006/RAL 5017	B47 RAL 1023/RAL 9017	B72 RAL 5017/RAL 7042	B76 RAL 5022/RAL 9003	B77 RAL 9006/RAL 9017
						
B104 RAL 9016/RAL 9017	B115 RAL 9016/RAL 7016	B107 RAL 9016/RAL 7016	B86 RAL 3020/9016	B01 RAL 9006/RAL 5017	B18 RAL 1023/RAL 9017	B23 RAL 5017/RAL 9016
						
B106 RAL 9016/RAL 7016	B112 RAL 9016/RAL 7043	B91 RAL 5017/RAL 9016	B92 RAL 1023/RAL 9017	B111 RAL 9016/RAL 7016	B11 RAL 1023/RAL 9017	B88 RAL 5017/RAL 9016
						
B12 RAL 3020/RAL 9016	B113 RAL 3020/RAL 9017	B33 RAL 6024/RAL 9006	B34 RAL 3020/RAL 9006	B35 RAL 6024/RAL 9006	B36 RAL 6024/RAL 9016	B37 RAL 3020/RAL 9016
						
B79 RAL 1023/RAL 9004	B102 RAL 3020/RAL 9016	B87 RAL 3020/RAL 9016	B19 RAL 9006/RAL 6024	B30 RAL 7035/RAL 6024	B69 RAL 9006/RAL 9017	B94 RAL 3020/RAL 9004
						
B96 RAL 9006/RAL 1023	B97 RAL 9006/RAL 3020	B93 RAL 9006/RAL 9004	B03 Goldfarbend/ gold colored	B50 RAL 1023	B80 RAL 9006	B85 RAL 3020
						
B95 RAL 5017	B105 RAL 9016	B108 RAL 9017	B119 RAL 5017/RAL 9016			

 Touch surface and pictograph on request

14 NOMINAL VOLTAGE

24 VDC

36 VDC

72 VDC

110 VDC

VDC

15 QUICK CONFIGURATION: LIGHT AND TONE SIGNALS

Functionality via pin assignment


If the pushbutton is pressed applies:

LED: duration of operation with 1 sec. minimum pulse

OUT: Duration of operation with 0.5 sec. minimum pulse

Change color and position


(first color is off when actuated) for rail vehicles according to EN 14752



4pole

Not pressed


Pressed



L1

L2


Add red light signal



5pole

Not pressed

Pressed



L1

L3

Orientation tone
3,8 kHz 0,05 Sek. 0,5 Hz

Confirmation tone
3,5 kHz 0,5 Sek. 1-time

Orientation and
confirmation tone

without
tone

**FINALIZE
CONFIGURATION PAGE 9**

16 INDIVIDUAL SELECTION OF FUNCTIONS

Light Signal	Display	Light Signal	Display
L0		L3 6 green LEDs 6 red LEDs	
L1 6 green LEDs		L5 12 red LEDs	
L2 6 red LEDs		L6 12 green LEDs	

Tone Signal A	Frequency	Duration	Interval	Description
A0	-	-	-	without tone
A1	3,5 kHz	0,5 Sec.	1 Hz	Confirmation tone
A2	3,8 kHz	0,05 Sec.	0,5 Hz	Orientation tone
AX	kHz	Sec.	Hz	

Circuit diagrams see page 7

red LEDs exchanged for yellow LEDs (L2, L3, L5)

Function 1			not pressed						pressed					
Vin	In1		LED-Light Signal				Tone Signal		LED-Light Signal				Tone Signal	
1	0		L0	L1	L2	L3	A0	A1	L0	L1	L2	L3	A0	A1
			L5	L6			A2	AX	L5	L6			A2	AX



Function 2			not pressed						pressed					
Vin	In1		LED-Light Signal				Tone Signal		LED-Light Signal				Tone Signal	
1	1		L0	L1	L2	L3	A0	A1	L0	L1	L2	L3	A0	A1
			L5	L6			A2	AX	L5	L6			A2	AX

From function 3 a 5-wire connection is necessary

Function 3				not pressed						pressed					
Vin	In1	In2		LED-Light Signal				Tone Signal		LED-Light Signal				Tone Signal	
1	0	1		L0	L1	L2	L3	A0	A1	L0	L1	L2	L3	A0	A1
				L5	L6			A2	AX	L5	L6			A2	AX

Function 4				not pressed						pressed					
Vin	In1	In2		LED-Light Signal				Tone Signal		LED-Light Signal				Tone Signal	
1	1	1		L0	L1	L2	L3	A0	A1	L0	L1	L2	L3	A0	A1
				L5	L6			A2	AX	L5	L6			A2	AX

17 CONNECTION CABLES

65) TE Mini-Universal MATE-N-LOK TE 794895-1 6pole (IP56/IP57)		23) ESCHA Ø8 Snap (max. 30 VDC) SP6 6pole (IP68)	
61) ESCHA M12 (max. 60 VDC) WAS4, 5pole (IP68)		E3) TE SUPERSEAL 1.5MM TE 282107-1 5polig (IP67)	
64) TE Mini-Universal MATE-N-LOK, TE 794805-1 4pole (IP56/IP57)		01) TE FASTIN-FASTON 250 TE 180901-0, 6,3 x 0,8 mm 4pole	
66) TE SUPERSEAL 1.5MM TE 282106-1 4pole (IP67)		00) TE CIRCULAR MATE-N-LOK, TE 925075, Ø 2,1 mm 4pole	
71) TE DEUTSCH DTM DTM04-4P 4pole (IP68)		02) TE FASTIN-FASTON 110 TE 626057-0, 2,8 x 0,8 mm 4pole	
60) ESCHA M8/Ø8 Snap (max. 60 VDC) SSFP4 4pole (IP68)		8S) TE ULTRAFast 250 2-520184-2, 6,3 x 0,8 mm	
8A) with wire-end sleeve		Customer specific	

PIN ASSIGNMENT

PIN 1:	Vin
PIN 2:	In1
PIN 3:	GND
PIN 4:	OUT
PIN 5:	In2
PIN 6:	In3/OUT2

18 CONNECTION LINE

[ACCORDING TO EN 45545-2 AND UN/ECE R118]

L = ca. 160 mm L = mm (minimum length 160 mm)